

Brakes

Electromagnetically Released System

For combination with
 DC-Micromotors:
 2342, 2642, 2657, 3242, 3257, 3557, 3863
 Brushless DC-Servomotors:
 2444, 3056, 3564, 4490

Series MBZ

	MBZ	12 V	22 V	24 V	
Nominal coil data at 20°C					
Supply voltage (DC) ±10%	U_N	12	22	24	Volt
Resistance	R	24	81	96	Ω
Current	I	0,50	0,27	0,25	A
Power	$P_{2 \text{ max.}}$	6	6	6	W
Mechanical response times ¹⁾					
Coupling time		13			ms
Disconnection time		27			ms
Static torque rating ²⁾					
Static torque rating ²⁾		400			mNm
Moment of inertia		10			gcm ²
Max. permissible speed					
Max. permissible speed		16 000			rpm
Temperature range: ³⁾					
Operating temperature		- 5...+ 120			°C
Storage temperature		-25...+ 120			°C
Weight					
Weight		50			g

- ¹⁾ Depending on the requirements, a Switch-off voltage-limitation function can be applied using an anti-parallel diode, varistor or other. However, this will influence the brake switching time.
²⁾ Under dry operation conditions, absolutely oil-free.
³⁾ Non condensing atmosphere.

Features

The brakes are designed as DC operated permanentmagnet single-surface brakes characterised by the fact that the braking effect is produced by a permanentmagnetic field (electromagnetically released system). This means that the required braking force is generated when voltage is removed.

In order to neutralise the braking effect, the permanentmagnetic field is counteracted by an opposing electromagnetic field.

The brakes are intended only for use as holding brakes (unsuitable for braking rotating motor shaft).

Full product description

- Examples:
3242G024CR MBZ22V

